



DECTEL

DR4024



FREQUENCY/COVERAGE

- Frequency bands coverage: EU/AU/NZ, US/CA, LATAM, TW
- Up to 50m indoor and 300m outdoor
- Receiver sensitivity: -92dBm
- 2 internal omni-directional antennas
- Support for external antennas using SMB connectors

GENERAL FEATURES

- Worldwide DECT support
- 1900 -1906 MHz (DECT) Thailand and customized frequency bands by software
- Power Level : 10mW average per channel at antenna connection
- Extending the DECT coverage
- Supports automatic handover of calls between cells
- Handling of 2 active calls simultaneously
- Up to 6 repeaters per base station
- Automatic registration method

STANDARDS/APPROVALS

- The DECT repeater is designed in accordance with the Digital Enhanced Cordless Telecommunications (DECT) standard
- The DECT repeater is compliant with:
 - TBR6, TBR22 (Generic Access Profile, GAP)
 - ETS 300 700 - ETSI Wireless Relay Station Specification

DESIGN/SIZE

- Indoor cabinet
- Manual mounting kit
- Easily mounted on walls
- Size: 120(W) x 35(D) x 135(H)mm

POWER SUPPLY

- 230 VAC and 110 VAC versions available

LED INDICATOR

- Radio link quality indication



International Business Communications Co.,Ltd.
1 Soi Bangna-Trad 14, Bangna-Trad Rd., Bangna-Trad,
Bangkok 10260, Thailand.

Tel: +66 (0) 2398 4848 Fax: +66 (0)2 744 4566

Email : info@ibiz-com.com